



### INSULATING GLOVES (Class 0)

Article No.: 67255AV802

Made with special grade natural rubber compounds for assured electrical protection. With superior anatomical construction results in lower hand fatigue. Higher flexibility for long duration wear comfort. Packed in opaque UV resistant bags and individual boxes for product protection. Each glove is inspected/tested for electrical insulation. Manufactured on a purpose built production line.



#### SPECIFICATION

Elastomer	: Natural rubber
Thickness	: 1.0 mm
Lining	: Unlined chlorinated
Former	: Plain smooth, CEI
Cuff Type	: Straight
Exterior	: Chlorinated
Colour	: Red
Type/Category	: Category A, C
Proof test voltage AC	: 5000 V
Max. use voltage AC	: 1000 V

#### APPLICATION

- For power companies (utilities)
- Electrical workshops
- Insulation
- Maintenance and Repairs involving High Voltage Equipment

#### DIMENSIONS

SIZE	PALM	WRIST	CUFF	LENGTH
8	206	206	379	360
8 1/2	217	217	379	360
9	227	227	392	360
9 1/2	243	243	395	360
10	251	251	396	360
10 1/2	266	266	403	360
11	282	282	405	360

Internal circumference in mm,+/- 10

Tolerance +/- 15 mm

- 100% QC Inspection
- Compliant to EN 60903:2003
- Produced at an ISO 9001:2015/ISO 14001:2015 accredited facility
- Compliant to PPE Regulation (EU) 2016/425

Doc. Control:	Rev.:	Date:
	3.2	April 13, 2016

This Article Data Sheet (ADS) is designed and produced by FLOWTRONIX (FT) covered under the intellectual property law. Any reproduction in whole or in part is strictly prohibited without written approval.

